# CAVIUS





















PRODUCT TYPE: SMART REMOTE WITH BUILT IN REMOTE CONTROL

PRODUCT NUMBER: 9001-001

## PRODUCT DATA:

#### PRODUCT TYPE:

Smart remote with emergency light.

#### **USAGE:**

Designed to alert with a rapid flashing warning light, vibration and buzzing when alarming and to remote control the CAVIUS Wireless Alarms Family. Torch function to find escape routes at night.

#### **OPERATION AC/DC:**

DC

#### **BATTERY TYPE:**

3 x DURACEL AAA batteries supplied with the Smart Remote.

#### INTERLINK FREQUENCY:

868MHZ

#### RANGE:

Minimum 100m in open field as a receiver, and within short range to silence an alarm. Range depends on the building materials and will need to be tested in each individual case.

#### LOW BATTERY INDICATION:

A short acoustic beep will sound to notify a low battery voltage.

#### INSTALLATION:

The body of the remote has a build-in magnet so that the remote can be installed on metal surfaces.

A lanyard can also be added to the end of the product so the remote can hang from a hook.

#### FLASHLIGHT:

Alarm conditions is indicated by a stroboscopic flashlight. A normal flashlight can also be activated by pressing the side button.

Flashlight will flash at 2 Hertz (2 times each second) to avoid photo sensitive epilepsy to be triggered.

#### **PUSH BUTTON:**

The Smart Remote is equipped with 3 switches: Sliding learn switch to connect to other alarms in the wireless family. Test/hush button at the end. Torch button on the side.

#### WARRANTY:

1 year



PRODUCT TYPE: SMART REMOTE WITH BUILT IN REMOTE CONTROL

## **PRODUCT DATA:**

#### **OPERATING TEMPERATURE:**

+4°C to +38°C (tested from 0 degrees to 55 degrees).

#### **OPERATING HUMIDITY:**

Up to 90% RH non-condensing

#### APPROVALS:

EN60065 EN300-220 ROHS REACH

#### **CE TESTING INSTITUTE:**

SGS

#### AWARDS:

Red Dot 2016 Design Awards



reddot award 2016

#### **ASSOCIATIONS:**

Cavius is member of GIFSID, manufacturers' association of domestic fire safety equipment

#### **STORAGE TEMPERATURE:**

-20°C to +60°C

#### STORAGE HUMIDITY:

Up to 93% RH non-condensing

## **QUALITY ASSURANCE:**

#### POWER CONSUMPTION:

100% tested

#### **BATTERY VOLTAGE AND INTERNAL RESISTANCE:**

100% tested

#### **ALARM FUNCTION:**

PRODUCT NUMBER: 9001-001

100% tested

#### INTERCONNECTION:

100% tested

#### **VISUAL APPEARANCE:**

100% tested

#### PACKING CONTENT:

100% tested

### CONTACT

www.cavius.com

## **MANUFACTURER**

Manufacturer: Cavius Aps, DK8600

## CAVIUS

